

IP65 RoHS Compliant CE

LED Garden Spot Light LED Spike Light



S83312



S83312+anti glare hood

- LED Colour Temperature
- 2700K • 3000K
 - 4000K • 6000K
- optics
- 8°/15°/25°/30°/45°/60°/90°

Housing color option

Aluminum anodized	Silver painting PAL9006
Mat black PAL9003	Dark grey RAL7012

Item No.	Light source	Lens beam angle(°)	Consumption (watt)	Input Voltage(V)	Life time
S83311	1x1W	8°/15°/20°/30°/45°/60°	1.1	DC12V/DC24V	02
S83311H	1x1W	8°/15°/20°/30°/45°/60°	1.3	AC120V/AC240V	02
S83312	1x2W	8°/15°/20°/30°/45°/60°	2.2	DC12V/DC24V	02
S83312H	1x2W	8°/15°/20°/30°/45°/60°	2.6	AC120V/AC240V	02
S83316	1x3W RGB3in1	30°/45°/60°	3.2	DC12V/DC24V	02
S83305COB	1x5W	15°/30°/45°	5.2	DC24V /100-240V	02

Optional accessories

a.Honecomb



b.Aluminum base






c.Aluminum spike



Outer Dimensions

Unit:mm



Material specifications

Housing&face cover:	Aluminum anodized finishing or powder painting
Glass:	Tempered glass, T=3mm
Lens:	Optical lens, efficiency>85%
Cable gland:	Copper and nickel coated
Gasket:	Tooling shaped seal
LED:	SMD LED
PCB:	Excellent heat conductivity aluminum, coefficient of Heat Conductivity2.0w/mk
Driver:	Constant current output single color LED=1-circuit output RGB 3in1 LED=3-circuit output
Operating temperature:	-20°C~40°C
Power cable:	H05RN-F 2x0.75mm², L=1m(low voltage) H05RN-F 3x0.75mm², L=1m(high voltage) H05RN-F 4x0.75mm², L=1m(for RGB)

