

▶ LED GARDEN SPIKE LIGHT & LED LAWN LIGHT



8383X



838110



▶ LED GARDEN SPOT LIGHT



8303X



830110

Housing color option


Grey painting RAL9007	Silver painting RAL9006
Matt black RAL9005	

LED Colour Temperature	optics
• 2700K • 3000K	• 8°/15°/25°/30°/45°/60°/90°
• 4000K • 6000K	


Material specifications

Housing	12#Die-casting powder coated aluminum, T=60-80um Adhesion of ISO class 1 / ASTM class 4B
Front cover	Stainless steel SUS 304 or 316
Bracket	Powder coated aluminum
Glass	Tempered glass, T=4mm
Lens	Optical lens, efficiency >85%
Cable gland	P-67 PG-9 PA66
Gasket	Molding shaped silicone double seal
Power cable	H05RN-F 2x0.75mm ² L=1m (low voltage) H05RN-F 3x0.75mm ² L=1m (high voltage) H05RN-F 4x0.75mm ² L=1m (for RGB)
Spike	PVC (grey or black)
Mounting base	Powder coated die-casting aluminum

Outer Dimensions Unit:mm



Outer Dimensions Unit:mm



Input voltage is according to LED bulb spec

Item No.	Light source	Lens beam angle (°)	Consumption (watt)	Input Voltage (V)	Ik rate
83831 83031	3x1W	8°/15°/20°/30°/45°/60°	3.2	DC12V/DC24V	04
83831H 83031H	3x1W	8°/15°/20°/30°/45°/60°	3.5	AC120V/AC240V	04
83832 83032	3x2W	8°/15°/20°/30°/45°/60°	6.2	DC12V/DC24V	04
83832H 83032H	3x2W	8°/15°/20°/30°/45°/60°	7.5	AC120V/AC240V	04
83834 83034	3x3W RG83n1	30°/45°/60°	3.2	DC12V/DC24V	04
838110 830110	GU10 socket	N/A	N/A	N/A	05