

Model: JY-2116R7- 2 Way

Floor recessed in 316L stainless steel. Resists strong climatic disturbances (saline air, treated water).

Technical Data

- Housing : Die-Cast Aluminum housing
- Diffuser : Tempered Glass
- Installation Type : Recessed
- Dimensions : D73 x H115mm
- Depth Required : 120mm
- Driver : Integral
- Ambient Temp. : -20°- +55°
- Adjustable : No
- Finish : SS 316+6063 Aluminum
- IP Rating : IP67
- IK Rating : IK10



Photometric Data

- Light Source : OSRAM COB LED
- CRI : 80/ 90
- CCT : 3000K / 4000K / 6000K
- Luminous Flux : 300Lm
- Light Efficiency : 60 Lm/W
- SDCM : SDCM>3
- Life hours : 50,000
- Beam Angle : 100°/180°



Electrical Details

- Power (W) : 5W
- Rated Voltage (V) : 220VAC-240VAC
- Power Factor : 0.9
- Input Type : Constant Current
- Electric Class : III
- Dimmable : On Request
- Protection : Short Circuit / overload / Overheat

APPLICATIONS

- Outdoor Residential
- Garden
- Outdoor illumination
- Outdoor Circulations
- Outdoor Lighting