

Model: IL-4401-20W

Sleek Round surface mounted on a ceiling with back-lit LED's that provides soft and glare free lights. The wide ranges are available in round. Suitable for Outdoor and Wet area applications. This gives a sense of luxury by improving overall aesthetic appearances.

Technical Data

- Housing : Die-Cast Aluminum housing
- Diffuser : Polycarbonate
- Installation Type : Surface Mounted
- Dimensions (DxH) : 248x70mm
- Driver : in-Built
- Ambient Temp. : -20° - +45°
- Adjustable : No
- Finish : White / Black
- IP Rating : IP65

Photometric Data

- Light Source : SMD LED
- CRI : 80 / 90
- CCT : 2700K / 3000K / 4000K
- Luminous Flux : 1800-2000Lm
- Light Efficiency : 90-100Lm/W
- SDCM : SDCM>3
- Life hours : 50,000
- Beam Angle : 120°



Electrical Details

- Power (W) : 20W
- Rated Voltage (V) : 220-240V AC, 50/60Hz
- Power Factor : 0.9
- Input Type : Constant Current
- Input Current : 500mA
- Electric Class : II
- Dimmable : On Request
- Protection : Short Circuit / Overload / Overheat

APPLICATIONS

- Outdoor and Wet Areas
- Arcades
- Service Area
- Residential Projects
- Commercial Projects