

## Model: IL-1504-18W

Trimless sleek surface panels and slim and can be mounted on a surface with back-lit LED's that provides soft and glare free lights. The wide ranges are available in round and square shapes. This gives a sense of luxury by improving overall aesthetic appearances.

### Technical Data

- Housing : Die-Cast Aluminum housing
- Diffuser : Polycarbonate
- Installation Type : Surface Mounted
- Dimensions (DxH) : 170x36mm
- Driver : Remote
- Ambient Temp. : -20° - +45°
- Adjustable : No
- Finish : White
- IP Rating : IP44



### Photometric Data

- Light Source : SMD LED
- CRI : 80 / 90
- CCT : 2700K / 3000K / 4000K
- Luminous Flux : 1620-1800Lm
- Light Efficiency : 90-100Lm/W
- SDCM : SDCM>3
- Life hours : 50,000
- Beam Angle : 120°



## Electrical Details

- Power (W) : 18W
- Rated Voltage (V) : 220-240V AC, 50/60Hz
- Power Factor : 0.9
- Input Type : Constant Current
- Input Current : 250mA
- Electric Class : II
- Dimmable : On Request
- Protection : Short Circuit / Overload / Overheat

## APPLICATIONS

- Hallway
- Corridor
- Service Area
- Residential Projects
- Commercial Projects