

Model: IL-8025-12W

Ceiling Cylindrical downlights with COB LED & beam angle options. The fixture comes with powder coated colors of Black / White. Competitively priced, high-quality products with wide range Wattages. LED outdoor Cylindrical light can be used by Lighting Designers & Architects to create fabulous night time aesthetics, security, entrance, balcony and arcade Areas.

Technical Data

- Housing : Die-Cast Aluminum housing
- Diffuser : Clear / Prismatic Glass
- Installation Type : Surface Mounted
- Dimensions (DxH) : 95x95mm
- Driver : Remote
- Ambient Temp. : -20° - +50°
- Adjustable : No
- Finish : White / Black
- IP Rating : IP65



Photometric Data

- Light Source : COB LED
- CRI : 80 / 90
- CCT : 2700K / 3000K / 4000K
- Luminous Flux : 1200Lm
- Light Efficiency : 100Lm/W
- SDCM : SDCM>3
- Life hours : 50,000
- Beam Angle : 60°



Electrical Details

- Power (W) : 12W
- Rated Voltage (V) : 220-240V AC, 50/60Hz
- Power Factor : 0.9
- Input Type : Constant Current
- Input Current : 350mA
- Electric Class : II
- Dimmable : On Request
- Protection : Short Circuit / Overload / Overheat

APPLICATIONS

- Balcony
- Entrance Porch
- General Lighting
- Residential Projects
- Commercial Projects